DigitalMedia™ Solutions Multiple Options for Different Situations

Check out the below chart to see some of the key differentiators between the different series of products within the DigitalMedia famiy of products.

	DM Lite™ system	DMPS Lite™ System	DMPS	DM [®] System	DM NVX® AV over IP
Use Case	Point to Point	Multi-Points to Point	Multi-Source to Display	Matrix to Display	IP Distribution of Video to Display
Distance	230 ft (70m)@ 1080 130 ft (40m)@ 4K/UHD	230 ft (70m)@ 1080 130 ft (40m)@ 4K/UHD	330 ft (100m)	330 ft (100m)	330 ft (100m)
Infrastructure	CatX	CatX	CatX (HDBaseT® Alliance spec)	CatX (HDBaseT® Alliance spec)	IP Cat5e
Runs on Existing Network Infrastructure	×	×	×	×	✓
Does not require configuration or programming	~	 Image: A second s	 Image: A second s	×	×
Built in Switching	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Ideal for BYOD/Portable Sources	✓	 Image: A second s	\checkmark	\checkmark	~
Ideal for Static Sources	×	\checkmark	\checkmark	\checkmark	\checkmark
Integrated 3-Series® Processor	×	×	 Image: A second s	×	×
Integrated DSP SKUs	×	×	v	×	V
USB Signal Routing (KVM)	×	×	 ✓ 	✓	v
Integrated Amplifier SKUs	×	✓	✓	×	×
Remotely Manageable	×	 ✓ 	~	v	 ✓
Integrated Amplifier SKUs	×	✓	v	×	×
Card/Chassis Form-Factor	×	×	×	v	v

While the DM Family's features can seemingly overlap, these categories are key differentiators when choosing the correct solution.